

# Panel-Loc Plus™

Wall and Roof Panel



## Superior *durability* with an attractive appearance

Panel-Loc Plus gives residential, agricultural, and light commercial projects the protection of steel with an attractive appearance. It features an extra striation on top of the rib to give it superior durability and protection against extreme weather. Panel-Loc Plus is available in 3 qualities: Standard, Prime, and Ultra.

- Engineered with a Siphon Groove to minimize leaks.
- Wide fastening surface for easy application.
- Unique lap groove hides the overlap giving a smooth, clean appearance.



RECOMMENDED <b>2½:12</b> PITCH AND ABOVE	<b>29</b> OR <b>26</b> GAUGE	<b>36"</b> OVERALL COVERAGE	<b>¾"</b> MAXIMUM RIB HEIGHT
---	---------------------------------------	-----------------------------------	------------------------------------



CENTRALSTATESMFG.COM

Copyright © 2021, Central States Manufacturing, Inc. All Rights Reserved.  
CentralGuard® is a trademark of Central States® Manufacturing, Inc.  
Galvalume® is a registered trademark of BIEC International, Inc.

CE FLYR\_PLP\_210712

**DO NOT USE THIS DIGITAL COLOR CHART FOR COLOR MATCHING.**

This digital color chart is intended to be viewed on computer monitors to show a wide range of colors available. Colors will vary depending on your computer monitor and monitor settings. Please ask for a physical color chart to view colors, and a metal sample for color matching purposes.



**Black** STANDARD | PRIME | ULTRA  
**Charcoal** STANDARD | PRIME | ULTRA  
**Pewter** PRIME  
**Gray** STANDARD | PRIME | ULTRA  
**Alamo** STANDARD | PRIME | ULTRA  
**Brilliant** STANDARD | PRIME | ULTRA

ULTRA may not be available in all locations.

Trim in 29ga only.

Trim in 29 ga only.



Choose CentralGuard for the best protection and a lifetime warranty.

# Panel-Loc Plus™

## Color Selection Tool



centralstatesmfg.com

\*Contact your salesperson for accurate pricing. † Color variation between orders is normal and not cause for rejection. ‡ Weathering and appearance variation, including color, sheen, and spangle, is common in non-painted materials and is not a cause for rejection. For consistent appearance, choose a paint-finished product.

Colors on this chart are close representations of actual metal color, limited by printing and viewing conditions. Color matching optimized for outdoor viewing.

E CHRT\_PLPL\_220101

**Forest**  
STANDARD | PRIME | ULTRA



**Hunter**  
STANDARD | PRIME | ULTRA



**Colony**  
PRIME

Trim gauge varies by location




**Crimson**  
PRIME | ULTRA



**Rustic**  
STANDARD | PRIME | ULTRA



**Burgundy**  
STANDARD | PRIME | ULTRA



**Gallery**  
PRIME | ULTRA



**Ocean**  
PRIME | ULTRA

Trim in 29ga only.



**Ivory**  
PRIME

Trim in 29 ga only.



**Light Stone**  
STANDARD | PRIME | ULTRA



**Desert**  
PRIME

Trim in 26 ga only.



**Taupe**  
STANDARD | PRIME | ULTRA



**PREMIUM COLOR**

Fluoropon® 70% PVDF  
20-year Warranty


**Copper Metallic\*†**  
PRIME



Clear acrylic coating  
**Galvalume®‡**  
STANDARD | PRIME | ULTRA



**Burnished Slate**  
STANDARD | PRIME | ULTRA



**Brown**  
STANDARD | PRIME | ULTRA



**Tan**  
STANDARD | PRIME | ULTRA



# Choose CentralGuard® for the best protection and a lifetime warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Available on our Prime and Ultra panels, the CentralGuard name is a guarantee that you have the best protection and a lifetime paint warranty.


Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

	STANDARD	<b>OUR BEST SELLER!</b> <b>PRIME</b> CentralGuard	<b>ULTRA</b> CentralGuard
<b>FADE PROTECTION</b>			
Paint Warranty	40-YEAR	<b>LIFETIME</b>	<b>LIFETIME</b>
Paint Thickness	THICK .90 mil	<b>THICKER 1.0 mil</b>	<b>THICKER 1.0 mil</b>
Fade Warranty	30-YEAR	30-YEAR	30-YEAR
Fade Protection	✓	✓✓	✓✓
<b>RUST BLOCKING</b>			
Advanced Rust Blocking	-	✓	✓
Perforation Warranty	-	20-YEAR	20-YEAR
Substrate Thickness	1.12 mil	1.60 mil	1.60 mil
<b>DENT RESISTANCE</b>			
Advanced Dent Resistance	-	✓	✓✓
Steel Thickness	THIN	THICK	THICKEST
Steel Gauge	29 ga.	29 ga.	26 ga.

*Panel-Loc Plus features UL2218 approval for impact resistance and may qualify for a homeowners insurance discount. See your local insurance agent for qualifications.*

## Siphon Groove

Panel-Loc Plus has two vertical edges, the overlap and the sidelap. The sidelap edge has a specific bend in the last major rib, called a siphon groove. When the overlap edge is installed on top of the sidelap edge, it creates an air gap that prevents water from wicking under the panel. Panels should be installed with the overlap facing away from the prevailing wind.



Find more information at  
[centralstatesmfg.com](http://centralstatesmfg.com)

## MINIMUM SPECIFICATIONS FOR ULTRA AND PRIME PAINTED PANELS

### GAUGE

Ultra 26 ga. | Prime 29 ga.

### STEEL THICKNESS

Ultra 0.0185" | Prime 0.0150"

### PAINT THICKNESS

Top coat paint: .70 mil  
Top coat primer: .30 mil  
Bottom coat backer: .35 mil  
Bottom coat primer: .35 mil

### TOTAL THICKNESS

Ultra 0.0202" | Prime 0.0167"

### RUST PROTECTANT SUBSTRATE

Galvalume® AZ50

### STEEL STRENGTH

80,000 PSI min

### PAINT SYSTEM

SMP

### WARRANTY

Lifetime limited paint adhesion  
30-yr. chalk and fade  
20-yr. Galvalume perforation

## TESTING & APPROVALS

### TESTING

TAS 100-95 Wind Driven Rain Test  
TAS 125-03 Uplift Resistance Test, 29 ga. Prime only  
ASTM-E455 Diaphragm Shear Standard Test, 26 ga.  
ASTM-E455 Diaphragm Shear Standard Test, 29 ga.

### APPROVALS

UL2218 UL Approval, Impact Resistance, Class 4  
UL580 UL Approval, Uplift Resistance, Class 90  
UL790 UL Approval, Fire Resistance, Class A  
RC-325 Texas Windstorm Approval, 29 ga. Over Wood Purlins  
RC-326 Texas Windstorm Approval, 29 ga. Over Decking  
FL14026 Florida Approval, Roof Panel Over 1<sup>5</sup>/<sub>32</sub>" Plywood (HVHZ, Miami-Dade Approved)  
FL14026 Florida Approval, Roof Panel Over 1<sup>5</sup>/<sub>32</sub>" Plywood (NON-HVHZ)  
FL14026 Florida Approval, Panel Over 2x4's (NON-HVHZ)